

Durable woven polyester fabric combined with a water resistant matte surface to produce exceptional printed resolution and high definition. Heavy and water resistant photo fabric that have no curl/crack under the tension. With lightness and softness of the material, it can be installed and displayed quickly and conveniently. Universally compatible with Eco-solvent, Mild-solvent and True-solvent ink.

## Application

■ Short term outdoor display	■ Roll up banner	■ POS	■ Synthetic Canvas
■ Tensioned Banner	■ Vertical Blind	■ Roller Blind	■ Exhibition Graphics

## Compatible Printers

Mimaki(JV3,JV5)	Vutek(UltraVu®)	Roland(SJ,AJ)	Mutoh(Rockhopper, spitfire)
★★★★★	★★★★★	★★★★★	★★★★★

## Technical data

Base material	100% woven polyester	Compatible Ink	Solvent/Eco/Mild solvent ink
Denier	150 x 600	Ink limit	200%
Total weight(g/m <sup>2</sup> )	192	Surface finish	Matt
Tolerance	±2	Optimum printer temp.	70°F (21 °C)
Thickness(μm)	260	Relative humidity (RH)	20~60%
Tolerance	±2	PVC Free	O
Threads per Inch	38 T	Fire Retardant	X
Color(CIE Mesearment)	L*:96 a*:1.2 b*:-6.5	Water resistant	O
Tensile strength (Kg/m <sup>2</sup> )	MD: 112, TD: 74		

## Roll Specification

Width	Gross Weight / roll (Kg/roll)	Roll length	33 yds (30meter)
36" (914mm)	6.8	Diameter of Core	3 inch
42" (1050mm)	7.8	Thickness of Core	4 mm
50" (1270mm)	9.3		
54" (1370mm)	10.0		
60" (1520mm)	11.0		

## Performance features

- 1) Compatible with Solvent, Eco-solvent and Mild-solvent ink
- 2) True color reproduction with rapid drying times
- 3) No edge-curl when under tension
- 4) Moisture resistant for short-term outdoor applications
- 5) Wrinkle-free performance, even after long-term storage.
- 6) Durable, universal coating eliminates cracking of the ink layer due to stretching in tensioned or weighted applications.



Should you have any inquiries, feel free to contact us.  
 Tel) +44 (0)208 546 1717, Fax) +44 (0)208 546 1717  
 Email: sales@sslinkltd.co.uk, Web site: <http://www.sslinkltd.co.uk>