

100% polyester woven and heavy fabric with a premium surface coating that will excellently support heavy ink coverage with solvent based ink. Heavy and water resistant photo fabric that have no curl/crack under the tension. With the lightness and softness of the material, it can be installed and displayed easily and freely. It provides wide compatibility with any branded piezo or thermal type plotters using solvent based ink.

Application

■ Polyester Canvas	■ Hanging Banner	■ Exhibition Graphics	■ Roll up Banner
■ Tensioned Banner	■ Scroll Banner	■ Textile Blinds	■ Indoor/Outdoor signs

Recommended Printers

Mimaki(JV3,JV5)	Vutek(UltraVu®)	Roland(SJ,AJ)	Mutoh(Rockhopper, spitfire)
★★★★★	★★★★★	★★★★★	★★★★★

Technical data

Base material	100% polyester Woven fabric	Compatible Ink	Solvent/Eco solvent
Denier	600×600	Ink limit	250%
Total weight(g/ m²)	265	Surface finish	Matt
Tolerance	±2	Optimum printer temp.	70°F (21 °C)
Thickness(µm)	380	Relative humidity (RH)	20~60%
Tolerance	±2	PVC Free	O
Threads per Inch		Fire Retardant	X
Color(CIE Mesearment)		Water resistant	O
Tensile strength (Kg/mm²)			

Roll Specification

Width	Gross Weight / roll (Kg/roll)	Roll length	33 yds (30meter)
36" (914mm)	8.83	Diameter of Core	3 inch
50" (1270mm)	12.04	Thickness of Core	4 mm

Performance features

- 1) Compatible with Solvent, Eco-solvent, Mild-solvent ink
- 2) True color reproduction with rapid drying times
- 3) No edge-curl when under tension
- 4) Moisture resistant for short-term outdoor applications - 2 to 3 weeks when printed with pigment inks
- 5) Wrinkle-free performance, even after long-term storage.
- 6) Durable, universal coating eliminates cracking of the ink layer due to stretching in tensioned or weighted applications.



Should you have any inquiries, feel free to contact us.

Tel) +44 (0)208 546 1717, Fax) +44 (0)208 546 1717

mail: sales@sslinkltd.co.uk, Web site: http://www.sslinkltd.co.uk