SBLM

Solvent PET Backlit film, front print - Matte, 280 g

For Solvent based ink

A translucent, front-print Backlit film. Matte type and printable directly on the surface. It delivers an excellent colour and high intensity of illumination effect with Solvent Inks. Specially, brilliant advertising effect with illuminated signs. Used at trade shows, exhibitions and subway. In fact, it is very suitable for any type of signs with illumination indoor and outdoor use.

Application

■ Outdoor/Indoor signs	■ Iluminated showcases	■ Display exhibitions ■ Wide color display with light	
■ City billboards	■ Subway billboards	■ Available any kinds of illuminated display	

Compatible Printers

Mimaki(JV3,JV5)	Vutek(UltraVu®)	Roland(SJ,AJ)	Mutoh(Rockhopper, spitfire)
****	****	***	***

Technical data

Base material	PET	Compatible Ink	Solvent/Eco solvent
Total weight(g/ m²)	281	Ink limit	200%
Tolerance	±3	Surface finish	Matt
Total thickness(畑)	205	Optimum printer temp.	70°F (21 °C)
Tolerance	±3	Relative humidity (RH)	20~50%
Released Film(Paper)	х	Water resistant	0
Adhesive	х	Adhesive	Х
Tensile strength (Kg/mm²)	MD:53 , TD: 90		
Heat shrink rate (%)	MD: 0.1, TD: 0.1		

Roll Specification

Width	Gross Weight / roll (Kg/roll)	Roll length	30meter
42" (1067mm)	10.5	Diameter of Core	3 inch
50" (1270mm)	12.0	Thickness of Core	4 mm
54" (1370mm)	13.5	•	
60" (1520mm)	15.0		

Remark

- 1) MOQ (Minimum Order Quantity): 98 rolls / 2 pallets
- 2) 1 pallets = 7 rolls X 7 rolls (49 rolls)
- 3) Offer: FOB Pusan, South Korea
- 4) Estimated Delivery time: 7 days by Air

5~6 weeks by ship

5) When the defect on quality come up, we will replace that material by the new roll.



Feel free to contact us via contact points below if you have any questions Tel) +44 (0)208 546 1717, Fax) +44 (0)208 546 1717 Email: sales@sslinkltd.co.uk, Web site: http://www.sslinkltd.co.uk