

Thin woven polyester fabric combined with a water resistant matte surface to produce exceptional printed resolution and high definition. Light, soft and durable photo fabric that have no curl under the tension. Universally compatible with dye / pigmented waterbased ink. With lightness and softness of the material, it can be installed and displayed easily and freely.

### Application

■ Outdoor/Indoor signs	■ Banner Stand	■ Hanging banner display	■ Tensioned banner display
■ Flying banner	■ Short term Event Flag	■ Roll up Blinds	■ POP-up exhibits

### Compatible Printers

HP Designjet / Latex	Epson	Roland	Mimaki JV / Latex
★★★★★	★★★★★	★★★★★	★★★★★

### Technical data

Base material	100% polyester Woven fabric	Compatible Ink	Dye/Pigment
Denier	150 x 150	Ink limit	200%
Total weight(g/m <sup>2</sup> )	110	Surface finish	Matt
Tolerance	±2	Optimum printer temp.	70°F (21 °C)
Thickness(μm)	160	Relative humidity (RH)	20~60%
Tolerance	±2	PVC Free	O
Threads per Inch	60 T	Fire Retardant	X
Color(CIE Meseartment)	L*: 96 a*: 1.3 b*: -5.5	Water resistant	O
Tensile strength (Kg/mm <sup>2</sup> )	MD: 54 , TD:35		

### Roll Specification

Width	Gross Weight / roll (Kg/roll)	Roll length	66 yds (60meter)
36" (914mm)	7.2	Diameter of Core	2 inch
42" (1050mm)	8.3	Thickness of Core	4 mm
50" (1270mm)	9.8		
54" (1370mm)	10.5		
60" (1520mm)	11.7		

### Performance features

<ol style="list-style-type: none"> <li>1) Compatible with dye and pigment inks.</li> <li>2) True color reproduction with rapid drying times</li> <li>3) No edge-curl when under tension</li> <li>4) Moisture resistant for short-term outdoor applications</li> <li>5) Wrinkle-free performance, even after long-term storage.</li> <li>6) Durable, universal coating eliminates cracking of the ink layer due to stretching in tensioned or weighted applications.</li> </ol>
--



Should you have any inquiries, feel free to contact us.  
 Tel: +44 (0)1372 459 942, Fax: +44 (0)1372 750 843  
 Email: sales@sslinkltd.co.uk, Web site: <http://www.sslinkltd.co.uk>