

**Product Data Sheet**

**W600KFR(V2)**

**Fire retardant & Clean cut heavy Photo Fabric, 230 gsm**

**For Dye, Pigment, UV ink**

Whiten and fire retardant polyester fabric combined with a water resistant matte surface to produce exceptional printed resolution and high definition. With excellent fire retardant effect, it provides the novel Clean Cut function, allowing it to be cut cleanly to size even using normal cutters - No loose thread. Thus it can be installed and displayed easily and freely. Heavy, soft and durable photo fabric that have no curl/crack under the tension. It provides wide compatibility with any branded piezo or thermal type plotters.

**Application**

■ Synthetic Canvas	■ Roll up Banner	■ Instant banner	■ Wall advertising
■ Outdoor, Indoor signs	■ Booth Display	■ Textile (Roll up) Blinds	■ POP-up exhibits

**Compatible Printers**

HP Designjet / Latex	Epson	Roland	Mimaki JV / Latex
★★★★★	★★★★★	★★★★★	★★★★★

**Technical data**

<b>Base material</b>	100% polyester Woven fabric	<b>Compatible Ink</b>	Dye/Pigment/UV ink
<b>Denier</b>	150 x 600	<b>Surface finish</b>	Matt
<b>Total weight(g/m²)</b>	230	<b>Ink limit</b>	250%
<b>Tolerance</b>	±2	<b>Optimum printer temp.</b>	70°F (21 °C)
<b>Thickness(µm)</b>	280	<b>Relative humidity (RH)</b>	20~60%
<b>Tolerance</b>	±2	<b>PVC Free</b>	○
<b>Threads per Inch</b>	38 T	<b>Fire Retardant</b>	○
<b>Color (CIE Measurement)</b>	L*: 92.94, a*: 0.84, b*: -4.60	<b>Water resistant</b>	○
<b>Tensile strength (Kg/mm²)</b>	MD: 113 , TD: 75	<b>Clean cut</b>	○

**Roll Specification**

<b>Width</b>	<b>Gross Weight / roll (Kg/roll)</b>	<b>Roll length</b>	33 yds (30meter)
36" (914mm)	7.4	<b>Diameter of Core</b>	2 inch , 3inch
42" (1067mm)	8.6	<b>Thickness of Core</b>	4 mm
50" (1270mm)	10.3		
54" (1370mm)	11.1		
60" (1520mm)	12.3		

**Remark**

1) Compatible with dye and pigment inks. 2) Outstanding Fire Retardant Function. 3) No edge-curl when under tension 4) Moisture resistant for short-term outdoor applications 5) Wrinkle-free performance, even after long-term storage. 6) True color reproduction with rapid drying times
--



Should you have any inquiries, feel free to contact us.  
Tel: +44 (0)1372 459 942, Fax: +44 (0)1372 750 843  
W: www.sslinkltd.co.uk, E: sales@sslinkltd.co.uk