

100% polyester woven fabric with a "universal" surface coating that will support heavy ink coverage with water based ink. Heavy and water resistant photo fabric that have no curl/crack under the tension. With the lightness and softness of the material, it can be installed and displayed easily and freely. It provides wide compatibility with any branded piezo or thermal type plotters using water based ink.

Application

■ Polyester Canvas	■ Hanging Banner	■ Exhibition Graphics	■ Roll up Banner
■ Tensioned Banner	■ Scroll Banner	■ Textile Blinds	■ Indoor/Outdoor signs

Compatible Printers

HP Designjet	Epson	Cannon	Roland
★★★★★	★★★★★	★★★★★	★★★★★

Technical data

Base material	100% polyester Woven fabric	Compatible Ink	Dye/Pigment
Denier	150 x 600	Ink limit	250%
Total weight(g/m ²)	183	Surface finish	Matt
Tolerance	±2	Optimum printer temp.	70°F (21 °C)
Thickness(μm)	250	Relative humidity (RH)	20~60%
Tolerance	±2	PVC Free	O
Threads per Inch	38 T	Fire Retardant	X
Color(CIE Mesearment)	L*:92 a*:-0.88 b*:1.73	Water resistant	O
Tensile strength (Kg/mm ²)	MD: 112 , TD: 74		

Roll Specification

Width	Gross Weight / roll (Kg/roll)	Roll length	33 yds (30meter)
24" (610 mm)	4.1	Diameter of Core	2 inch
36" (914mm)	6.2	Thickness of Core	4 mm
44" (1118mm)	7.4		
50" (1270mm)	8.4		
54" (1370mm)	9.0		
60" (1520mm)	10.0		

Performance features

- 1) Compatible with dye, pigment and UV ink.
- 2) True color reproduction with rapid drying times
- 3) No edge-curl when under tension
- 4) Moisture resistant for short-term outdoor applications
- 5) Wrinkle-free performance, even after long-term storage.
- 6) Durable, universal coating eliminates cracking of the ink layer due to stretching in tensioned or weighted applications.



Should you have any inquiries, feel free to contact us.
 Tel) +44 (0)208 546 1717, Fax) +44 (0)208 546 1717
 Email: sales@sslinkltd.co.uk, Web site: <http://www.sslinkltd.co.uk>