

100% polyester fabric for single side inkjet printing that is woven with black and white yarn for 60% ~ 70% blockout effect on the back. Combined with a water resistant matte surface to produce exceptional printed resolution and high definition. Light, soft and durable photo fabric that have no curl under the tension. Universally compatible with dye / pigmented waterbased ink. It doesn't fray by cutting even normal knife so it can be installed and displayed easily and freely.

### Application

■ Roller banner stand	■ Roller blinds	■ Curtain	■ Tensioned banner display
■ Indoor banner	■ Wall advertising	■ POP-up exhibits	■ Instant banner

### Compatible Printers

HP Designjet / Z series / Latex	Epson	Roland/Mimaki	Cannon
★★★★★	★★★★★	★★★★★	★★★★★

### Technical data

Base material	100% polyester Woven fabric	Compatible Ink	Dye/Pigment/UV ink
Denier	150 x 150	Surface finish	Matt
Total weight(g/m <sup>2</sup> )	204	Ink limit	250%
Tolerance	±2	Optimum printer temp.	70°F (21 °C)
Thickness(μm)	302	Relative humidity (RH)	20~60%
Tolerance	±2	PVC Free	O
Threads per Inch		Fire Retardant	X
Color (CIE Measurement)		Water resistant	O
Tensile strength (Kg/mm <sup>2</sup> )		Clean cut	O

### Roll Specification

Width	Gross Weight / roll (Kg/roll)	Roll length	33 yds (30meter)
24" (610mm)	4.5	Diameter of Core	2 inch
36" (914mm)	6.6	Thickness of Core	4 mm
50" (1270mm)	9.2		
60" (1520mm)	11.0		

### Remark

<ol style="list-style-type: none"> <li>1) Compatible with dye and pigment inks.</li> <li>2) Outstanding Fire Retardant Function.</li> <li>3) No edge-curl when under tension</li> <li>4) Moisture resistant for short-term outdoor applications</li> <li>5) Wrinkle-free performance, even after long-term storage.</li> <li>6) True color reproduction with rapid drying times</li> </ol>
--



Should you have any inquiries, feel free to contact us.  
 Tel) +44 (0)208 546 1717, Fax) +44 (0)208 546 1717  
 Email: sales@sslinkltd.co.uk, Web site: <http://www.sslinkltd.co.uk>