

Product Data Sheet**WPVC****Self adhesive vinyl – Matte, Clear back, 360 g****For Dye/pigment ink**

Clear-adhesive type, PVC CAL which is perfectly absorb water based ink, e.g. dye and pigment ink. It makes possible to print on a variety of wide format plotters. PVC delivers accurate colors and vivid results on its high-quality matt surface. Perfectly suited for all possible indoor displays and including long -term indoor applications on corrugated surfaces.

Application

■ Indoor signs	■ Trade show graphics	■ Window display	■ AD for Corrugated surface
■ Backlit display	■ Point-of-purchase displays	■ Booth display	

Compatible Printers

HP Designjet	Epson	Roland/Mimaki	Novajet
★★★★★	★★★★★	★★★★	★★★★

Technical data

Base material	Translucent PVC Film	Compatible Ink	Dye/Pigment
Total weight(g/ m²)	360	Ink limit	200%
Tolerance	±5	Surface finish	Matte
Total thickness(μm)	230	Optimum printer temp.	70°F (21 °C)
Tolerance	±5	Relative humidity (RH)	20~50%
Released film weight(g/ m²)	163	Life expectancy	Indoor: 1year Outdoor: 3months
Adhesive	Clear Adhesive	Water resistant	O
Released Film thickness(μm)	PET 75 μm		

Roll Specification

Width	Gross Weight / roll (Kg/roll)	Roll length	30meter
36"(914mm)	8.7	Diameter of Core	2 inch
50" (1270mm)	12.0	Thickness of Core	4 mm
60" (1520mm)	14.4		

Remark

1) MOQ (Minimum Order Quantity): 98 rolls / 2 pallets
2) 1 pallets = 7 rolls X 7 rolls (49 rolls)
3) Offer: FOB Pusan, South Korea
4) Estimated Delivery time: 7 days by Air 5~6 weeks by ship
5) When the defect on quality come up, we will replace that material by the new roll.



Feel free to contact us via contact points below if you have any questions

Tel) +44 (0)208 546 1717, Fax) +44 (0)208 546 1717

Email: sales@sslinkltd.co.uk, Web site: <http://www.sslinkltd.co.uk>