

Clear and white self-adhesive PP synthetic paper which perfectly absorbs water based ink, e.g. dye and pigment ink. Colour effect is excellent with Backlighting by light dispersion / Water-resistant. It makes possible to print on a variety of wide format plotters. 3C-SPC delivers accurate colors and vivid results on its high-quality Matt surface. It's excellent for indoor signage.

Application

■ Non-Light dispersion sign	■ Photo stickers	■ Graphic arts
■ Backlit display	■ Light dispersion signboards	■ Pictures for the digital camera etc

Recommended Printers

HP Designjet	Epson	Roland/Mimaki	Novajet
★★★★★	★★★★★	★★★★★	★★★★★

Compatible Printers

Base material	PP Synthetic Paper 80 μ m	Compatible Ink	Dye/Pigment
Total weight(g/ m²)	174	Ink limit	200%
Tolerance	±3	Surface finish	Matte
Total thickness(μm)	193	Optimum printer temp.	70°F (21 °C)
Tolerance	±3	Relative humidity (RH)	20~50%
Released film weight(g/ m²)	74	Life expectancy	Indoor: 1year Outdoor: 3months
Adhesive	Clear Adhesive	Water resistant	O
Released film thickness(μm)	PET 50 μ m		

Roll Specification

Width	Gross Weight / roll (Kg/roll)	Roll length	30meter
36"(914mm)	5.8	Diameter of Core	2 inch
50" (1270mm)	8.0	Thickness of Core	4 mm
60" (1520mm)	9.6		

Remark

1) MOQ (Minimum Order Quantity): 98 rolls / 2 pallets
2) 1 pallets = 7 rolls X 7 rolls (49 rolls)
3) Offer: FOB Pusan, South Korea
4) Estimated Delivery time: 7 days by Air 5~6 weeks by ship
5) When the defect on quality come up, we will replace that material by the new roll.



Feel free to contact us via contact points below if you have any questions
 Tel) +44 (0)208 546 1717, Fax) +44 (0)208 546 1717
 Email: sales@sslinkltd.co.uk, Web site: http://www.sslinkltd.co.uk